















st-team

## Akustoivat kiinnityspinnat

aura  
taite-  
seinät **120**

 Platinum 261 NCS S 4502-B	 Slate 262 NCS S 6502-B	 Steel 272 NCS S 7502-B	 Carbon 269 NCS S 8502-B	 Noir 279 NCS S 9000-N	 Espresso 274 NCS S 7010-Y70R	 Sandstone 273 NCS S 6005-Y50R	 Sable 263 NCS S 5010-Y30R
 Sunshine 265 NCS S 3050-Y10R	 Terracotta 276 NCS S 4050-Y70R	 Ruby 286 NCS S 2570-R	 Rose 266 NCS S 4030-R	 Celadon 268 NCS S 5020-B70G	 Jade 288 NCS S 7020-B50G	 Pastoral 278 NCS S 7020-G10Y	 Nautical 267 NCS S 7020-B10G
 Indigo 277 NCS S 8010-R90B	Osittaisia värieroja saattaa esiintyä eri toimituserien kesken. Sävyjen meleerausten vuoksi NCS-sävy on viitteellinen.						

Pintamateriaali: 100% polyamidi    
 Taustamateriaali: 100% kierrätetty polyesteri  
 Kangaslev.: 200 cm  
 Paino: 800 g/m<sup>2</sup>  
 Paksuus: 4,9 mm  
 Absorptioarvo: H, aw=0,15 (EN ISO 354 / EN ISO 11654)  
 Palosuojaus: C<sub>fl</sub>-s1, G, NCS (EN 13501-1)  
 Sisäilma (TVOC): < 0,1 mg/m<sup>3</sup> (EN ISO 16000)

120-100b